

# مشخصات فنی خش کن هوای فشرده لوپامات

## COMPAC

| Model          | Motor Power |     | Capacity            |        | Connection | Dew point<br>°C |
|----------------|-------------|-----|---------------------|--------|------------|-----------------|
|                | kW          | hp  | m <sup>3</sup> /min | cfm    |            |                 |
| Compac-900     | -           | 1/5 | 0.90                | 31.8   | 1/2"       | +3              |
| Compac-1.200   | -           | 1/5 | 1.20                | 4.4    | 1/2"       | +3              |
| Compac-1.800   | -           | 1/4 | 1.80                | 63.6   | 3/4"       | +3              |
| Compac-2.200   | -           | 1/4 | 2.20                | 77.7   | 3/4"       | +3              |
| Compac-2.600   | -           | 3/8 | 2.60                | 91.9   | 1"         | +3              |
| Compac-3.100   | -           | 3/8 | 3.10                | 109.6  | 1"         | +3              |
| Compac-3.700   | -           | 1/2 | 3.70                | 130.8  | 1"         | +3              |
| Compac-5.500   | -           | 3/4 | 5.50                | 194.4  | 1"         | +3              |
| Compac-6.500   | -           | 1   | 6.50                | 229.7  | 1 1/2"     | +3              |
| Compac-8.500   | -           | 2   | 8.50                | 300.4  | 2"         | +3              |
| Compac-11.000  | -           | 2   | 11.00               | 388.7  | 2"         | +3              |
| Compac-13.000  | -           | 2.5 | 13.00               | 459.4  | 2"         | +3              |
| Compac-17.800  | -           | 3   | 17.80               | 629.1  | 2"         | +3              |
| Compac-20.000  | -           | 4   | 20.00               | 706.8  | 2 1/2"     | +3              |
| Compac-25.500  | -           | 4   | 25.50               | 901.2  | 2 1/2"     | +3              |
| Compac-30.000  | -           | 5   | 30.00               | 1060.2 | 2 1/2"     | +3              |
| Compac-35.500  | -           | 6   | 35.50               | 1254.6 | 3"         | +3              |
| Compac-40.000  | -           | 7   | 40.00               | 1413.6 | 3"         | +3              |
| Compac-45.000  | -           | 7   | 45.00               | 1590.3 | 3"         | +3              |
| Compac-50.000  | -           | 10  | 50.00               | 1767.0 | DIN100     | +3              |
| Compac-60.000  | -           | 10  | 60.00               | 2120.4 | DIN100     | +3              |
| Compac-71.000  | -           | 12  | 71.00               | 2509.1 | DIN100     | +3              |
| Compac-80.000  | -           | 13  | 80.00               | 2827.2 | DIN100     | +3              |
| Compac-90.000  | -           | 15  | 90.00               | 3180.6 | DIN100     | +3              |
| Compac-106.000 | -           | 18  | 106.00              | 3746.0 | DIN125     | +3              |
| Compac-120.000 | -           | 20  | 120.00              | 4240.8 | DIN125     | +3              |
| Compac-140.000 | -           | 25  | 140.00              | 4947.6 | DIN125     | +3              |



- \* Air flow refers to the compressor performances. Working pressure: 7bar (16bar Max.)
- \* Inlet air temperature: 35 °C (45 °C Max.)
- \* Ambient temperature: 25 °C (45 °C Max.)
- \* Dew point: 3 °C (-22 atm)
- \* Inlet and outlet filters are included on dryers. Only in the COMPAC 11.000 and in the upper models, filters are additional without any extra charges.