

مشخصات فنی کمپرسور اسکرو لوپامات

LKV-CA, CAT, CATK

Type			CA		
Model	Motor Power		Capacity, FAD*		
	kW	hp	m ³ /min		
			7.5 barg	10 barg	13 barg
LKV 4 CA	4	5.5	0.58	0.49	0.42
LKV 5.5 CA	5.5	7.5	0.80	0.69	0.59
LKV 7.5 CA	7.5	10	1.19	1.02	0.86
LKV 11 CA	11	15	1.72	1.49	1.28
LKV 15 CA	15	20	2.53	2.19	1.85
LKV 18.5 CA	18.5	25	3.26	2.63	1.93
LKV 22 CA	22	30	3.82	3.20	2.48
LKV 30 CA	30	40	4.67	4.18	3.68
LKV 37 CA	37	50	6.01	5.32	4.62
LKV 45 CA	45	60	7.09	6.34	5.57
LKV 55 CA	55	75	9.24	8.13	6.67
LKV 75 CA	75	100	11.97	10.70	9.42



Type			CAT			
Model	Motor Power		Capacity, FAD*			Receiver volume
	kW	hp	m³/min			lt
			7.5 barg	10 barg	13 barg	
LKV 4 CAT	4	5.5	0.58	0.49	0.42	548
LKV 5.5 CAT	5.5	7.5	0.80	0.69	0.59	548
LKV 7.5 CAT	7.5	10	1.19	1.02	0.86	548
LKV 11 CAT	11	15	1.72	1.49	1.28	548
LKV 15 CAT	15	20	2.53	2.19	1.85	548

Type			CATK						
Model	Motor Power		Capacity, FAD*			Receiver Volume	Dryer Capacity		
	kW	hp	m³/min			lt	m³/min		
			7.5 barg	10 barg	13 barg		7.5 barg	10 barg	13 barg
LKV 4 CATK	4	5.5	0.58	0.49	0.42	548	0.88		
LKV 5.5 CATK	5.5	7.5	0.80	0.69	0.59	548	0.88		
LKV 7.5 CATK	7.5	10	1.19	1.02	0.86	548	1.67	1.67	0.88
LKV 11 CATK	11	15	1.72	1.49	1.28	548	2.58	1.67	1.67
LKV 15 CATK	15	20	2.53	2.19	1.85	548	2.58		



- * FAD: Free Air Delivery
- * FAD is measured according to ISO 1217, Rev. 3, Annex C- 1996
- * Lupamat reserves the right to alter the given technical data without prior notice.