

مشخصات فنی خشک کن هوای فشرده لوپامات

MKE

Model	Motor Power		Capacity		Connection	Dew point °C
	kW	hp	m ³ /min	cfm		
MKE-23	-	0.43	0.38	13.4	1/2"	+3
MKE-38	-	0.43	0.63	22.2	1/2"	+3
MKE-53	-	1/2	0.88	31	1/2"	+3
MKE-100	-	1/2	1.67	58.9	1/2"	+3
MKE-155	-	0.8	2.58	91	3/4"	+3
MKE-190	-	0.9	3.17	111.9	3/4"	+3
MKE-210	-	1.1	3.50	123.5	3/4"	+3
MKE-305	-	1.5	5.08	179.3	1 1/2"	+3
MKE-375	-	1.75	6.25	220.6	1 1/2"	+3
MKE-495	-	1.75	8.25	291.2	1 1/2"	+3
MKE-623	-	1.75	10.38	366.4	1 1/2"	+3
MKE-930	-	2	15.50	547.1	2"	+3
MKE-1200	-	2.5	20.00	706	2"	+3
MKE-1388	-	3.7	23.13	816.5	3"	+3
MKE-1800	-	4.2	30.00	1059	3"	+3
MKE-2500	-	5.5	41.67	1471	3"	+3
MKE-2775	-	6.2	46.25	1632.6	3"	+3
MKE-3330	-	7.5	55.50	1959.1	DN100	+3
MKE-3915	-	8.25	65.25	2303.3	DN100	+3
MKE-5085	-	10	84.75	2991.7	DN100	+3
MKE-5850	-	13.5	97.50	3441.7	DN100	+3
MKE-6975	-	15	116.25	4103.6	DN150	+3
MKE-7875	-	16	131.25	4633.1	DN150	+3
MKE-9000	-	20	150.00	5295	DN150	+3
MKE-10500	-	20	175.00	6177.5	DN200	+3
MKE-12500	-	25	208.30	7353	DN200	+3



- * Max. Working pressure: 16 bar
- * Max. Inlet air temperature: 50 °C
- * Max. Ambient temperature: 45 °C
- * Dew point: 3 °C (-22 atm)
- * Inlet and outlet filters are included on dryers. (up to Model MKE 2775)
- * All filters are equipped with automatic drain valve. (up to Model MKE 2775)